

	Production capabilities Namacor B.V.	
	Line I	Line II
Gauges	3.0 - 30.0 mm	1.50 - 6.0 mm
Widths	600 - 2,500 mm trimmed	910 - 2,000 mm trimmed
	max. 2,600 mm untrimmed	max. 2,050 untrimmed
Lengths	1,600 - 18,000 mm. Longer: upon request	1,600 - 9,000 mm
Max. Tensile & Yield	830 & 700 N/mm ²	630 & 430 N/mm ²
Min. Trimming	3.0 - 5.0 mm: 10.0 mm per edge	1.5 - 5.0 mm: 10.0 mm per edge
	≥ 5 mm: gauge + 5.0 mm per edge	5.0 - 6.0 mm: gauge + 5.0 mm per edge
Max. Trimming	3.0 - 10.0 mm: 240.0 mm	< 3.0 mm: max. 140.0 mm in total
	10.0 - 15.0 mm: 160.0 mm	3.0 - 5.0 mm: max. 100.0 mm in total
	15.0 - 20.1 mm: 90.0 mm	5.0 - 6.0 mm: max. 70.0 mm in total
	> 20.1 mm: no edge trimming	
Max. Coilweight	45 MT	45 MT
Inner Diameter of coil	580 - 890 mm	500 - 850 mm
Max. Bundle weight	25 MT	25 MT
Ink marking	Yes	Yes
Hard stamping	Yes	Yes
Products	HR Black, HR P&O, Floor Plate	HR Black, HR P&O, CR